



iData T2

Large screen high-performance terminal

Designed for field work environment

iData T2 is a large screen high-performance terminal with 4G network, which assure a faster data transmission rate and low network delay. With the help of 6.21-inch large HD screen, the device interaction become much easier. T2 is the dedicated practical mobile terminal for staffs who work outdoors environment, such as large-scale ports, exhibition arenas, etc.

Enterprise-level performance, verified quality in many industries

With industry-leading barcode scanning performance, repeatedly proven high performance and reliability, ultra-large capacity removable battery and comprehensive accessory support, the device is more suitable for staff operations than smartphones. It can help employees in all kinds of industries complete their work more efficiently.

6.21" large HD screen, the efficiency increases dramatically

More information can be displayed within the large screen, which lowers the mistouch rate during interaction with APPs. The efficiency of workers increase significantly in both reading or information input.

Powerful performance, ultra-long product lifespan

Equipped with octa-core 2.0GHz processor and 64GB(ROM)+4GB(RAM), iData T2 not only runs faster to support multitasking demand but also assures a longer lifespan to survive product upgrade for future business.



Receiving and
delivery



Meter-reading
management



Ticketing
management



Mobile
law-enforcement

T2 (4G) Technical Specifications

System Configuration

Processor	Octa-core 2.0GHz high-performance processor
Operating System	Android 12.0 (GMS)
Memory (ROM+RAM)	64GB + 4GB (standard)
SIM	Two out of three SIM card slots, support dual SIM and dual standby * Two out of three SIM card slots: two cards can be held at the same time, Nano SIM card + Nano SIM card / Nano SIM card +TF card
Expansion Slot	Micro SD card (up to 256 GB)
Display Screen	6.21-inch, resolution: 1520*720 pixels
Touch Screen	Industrial capacitive screen, support wet-hand operation/glove mode/multi-touch
Camera	16 megapixels rear camera + 0.3 megapixels sub-camera, support auto-focus/PDAF, 5 megapixels front camera
Flashlight	800mA flashlight
Keypad	5 keypads in total: side scan key *2, side power key *1, side $\pm$ volume key *2
Battery	3.85V lithium battery, with 4500mAh, detachable 3.85V lithium battery, with 4200mAh, detachable, support NFC
Audio	Built-in dual microphone
Charging Method	Type-C charging and pin port charging, support 18W fast charging
Reminder	High-power speaker/Vibration reminder/LED reminder/Audio reminder
Fingerprint Recognition	Support back fingerprint recognition
Vibrating Motor	Built-in vibrating motor
Sensors	G-sensor/Proximity sensor/Light sensor/Geomagnetic sensor/Gyroscope
Intercom Function (Optional)	Support one-button PTT calls

Structure Parameter

Dimension (L*W*D)	168mm*79mm*13.7mm
Weight	288g (including the battery)

Environmental Parameter

Working Temperature	-20°C - 60°C *Do not charge under low temperature conditions
Storage Temperature	-40°C - 70°C
Humidity	0 - 95% (no moisture condensation)
Drop Specification	Multiple drops to concrete floor from the height of 1.5m
Roller Drop Specification	1000 times of roller drops from a height of 0.5 meter
Ingress Protection	IP67
ESD Protection	$\pm$ 15KV (air discharge), $\pm$ 8KV (contact discharge)

Communication Interface

USB Interface	Type-C (with headset function) *1
OTG Interface	Support

Scanning Engine

Barcode Type	It can scan one-dimensional / two-dimensional barcodes
Scanning Accuracy	$\geq$ 3.33mil
Scanning Angle	Pitch: $\pm$ 60°; Skew: $\pm$ 45°; Tilt: 360°
View Angle	Horizontal: 44.3°, Vertical: 28.4°, Diagonal: 51°
Motion Error Tolerance	8m/s

Communication Transmission

WWAN (Network Frequency)	China & Eurasian version: 2G: B2/B3/B5/B8 3G: WCDMA: B1/B5/B8, CDMA BC0, TD-SCDMA: B34/B39 4G: FDD-LTE: B1/B3/B5/B7/B8/B20, TDD-LTE: B34/B38/B39/B40/B41 American version: 2G: B2/B3/B5 3G: B1/B2/B4/B5, CDMA BC0/BC1 (US) 4G: B1/B2/B3/B4/B5/B7/B12/B17/B28A/B28B/B41
WWAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/EVDO /WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
WLAN Function	Wi-Fi 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v/w (2.4G + 5G dual-band Wi-Fi), support fast roaming
Bluetooth	Bluetooth 5.0
GPS	GPS/AGPS/Beidou/Galileo/GLONASS/QZSS

NFC (Optional)

Working Frequency	13.56 MHz
Reading Distance	Within 60 mm
Communication Protocol	ISO14443A/14443B/15693

Development Support

Programming Language	Java
Development API	iScan API (Scanning Development Kits), Device API (Device Management/Configuration Development Kits), Android Standard Interface
Development Tool	Eclipse/Android Studio

Accessories

Standard Accessories	USB cable*1, power adapter*1, device-back strap*1, battery*1
Optional Accessories	Power adapter(fast charging), 2-in-1 charging cradle, multifunctional 5-slot base, hand strap*1, single charging cradle, bottom charger, 4-slot charging cradle, 4-slot battery charging cradle, fanny pack, protective film, Protective case

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



Official Website

WUXI IDATA TECHNOLOGY CO., LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center,
No.999 Gaolang East Road, Wuxi City, Jiangsu Province, P.R.C.

E-mail: sales@idataglobal.com

Website: www.idataglobal.com

Each product comes with a pack of practical and cost-effective accessories

USB Cable

Type-C to USB cable, 1m in length, support charging and data transmission



CHA-USBC-GNR

Battery

4500mAh, detachable design. Support NFC

4200mAh, detachable design, support NFC

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-T2-4500MA

CHA-BTRY-T2-4200MA

Device-back Strap

Attach on the device back to help you hold the device easily and firmly, avoid accidental drops



MNT-BS-T2


Power Adapter

Input voltage 100-240V, output 5V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR

ps: you may have one of the power adapters



CHA-PWAD-
GNR-5V2A-CN



CHA-PWAD-
GNR-5V2A-EU



CHA-PWAD-
GNR-5V2A-UK



CHA-PWAD-
GNR-5V2A-US



CHA-PWAD-
GNR-5V2A-AU

Improve management efficiency of devices and operational level of enterprises

Power Adapter (fast-charging)

Input voltage 100-240V, output 9V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR

ps: choose one that fits your local standard



CHA-PWAD-GNR-9V2A-EU

Battery

4500mAh, detachable design. Support NFC

4200mAh, detachable design, support NFC

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-T2-4500MA

CHA-BTRY-T2-4200MA

2-in-1 Charging Cradle

Support maximum charging of 1 main unit+1 battery at the same time. Match with multifunctional 5-slot base. Support plug types of China/Europe/UK/US/Australia



CHA-BTC21-T2

Multifunctional 5-slot Base

Support maximum charging of 5 units of 2-in-1 charging cradle at the same time. Support plug types of China/Europe/UK/US/Australia



CHA-MCRD5S-GNR

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



Official Website

WUXI IDATA TECHNOLOGY CO., LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center,
No.999 Gaolang East Road, Wuxi City, Jiangsu Province, P.R.C.

E-mail: sales@idataglobal.com

Website: www.idataglobal.com

Improve management efficiency of devices and operational level of enterprises

Bottom Charger

Bottom charger for the main unit, support charging for 1 device.
USB-A port, can connect with CHA-PWAD-GNR-5V2A-XX accessory



CHA-BTC-T2

Single Charging Cradle

Support charging for 1 main unit. Support plug types of
China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD1S-T2

4-slot Charging Cradle

Constituted by 4 CHA-CRD1S-T2, support maximum charging of 4
main units at the same time. Support plug types of
China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4S-T2

4-slot Battery Charging Cradle

Support maximum charging of 4 batteries at the
same time. Support plug types of
China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4B-T2

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



Official Website

WUXI IDATA TECHNOLOGY CO., LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center,
No.999 Gaolang East Road, Wuxi City, Jiangsu Province, P.R.C.

E-mail: sales@idataglobal.com

Website: www.idataglobal.com

T2 Optional Accessories for Portability

Accessories Guide

Improve device portability and comfort for users, boost working efficiency

Fanny Pack

Used to carry main units and other accessories. Can be tied to the waist or used as a crossbody bag



MNT-FP-GNR

Hand Strap

Wear on your wrist to carry the device, avoid accidental drops, and assure the safety of equipment



MNT-HS-GNR


T2 Optional Accessories for Protection

Accessories Guide

Lower risks of malfunction during usage, extend lifespan of devices

Protective Film

Protective film for touchscreen. It can protect the screen from cracking or being scratched in case there's any accidental drops or impact during usage



PRT-PTF-T2

Protective Case

Protective case for the main unit. It can prevent the malfunction of main unit in case there's any accidental drops or impact during usage



PRT-PTC-T2

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



Official Website

WUXI IDATA TECHNOLOGY CO., LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center,
No.999 Gaolang East Road, Wuxi City, Jiangsu Province, P.R.C.

E-mail: sales@idataglobal.com

Website: www.idataglobal.com