

# ZT510 Industrial Printers

## Taking The 105SLPlus To A New Level With Expanded Performance and Value

Designed to strike the ideal balance between performance and value, the ZT510 includes the core features you need in an industrial printer at a cost-effective price point. Building on the legacy of its industry-leading predecessor, the Zebra® 105SLPlus™, the ZT510 provides a proven, durable design and construction while adding advanced management and monitoring capabilities. That means you get 24/7 reliability to keep your operations running smoothly today, plus longevity and advanced functionality to power through every challenge in the years to come—all at an exceptional value.



### **Link-OS® for greater visibility, remote management and easier maintenance**

Zebra's highly intelligent, best-in-class Link-OS environment provides greater insight into the real-time status and functions of your printing processes. With Link-OS, you can use a single cloud-based application to manage routing, firmware updates, printer configuration and more, on-site or remotely. And applications like Virtual Devices, Profile Manager, Near Field Communication (NFC) and Print Touch make it easy to integrate, update and contact support.

### **Outstanding performance at exceptional value**

Zebra's industrial printers are well-known for their durability, fast print speed, long life span and unparalleled reliability. The budget-friendly ZT510 carries on that legacy, with:

#### **24/7 reliability to eliminate downtime**

You need printing systems that can support your critical processes and keep you ahead of increasing demands. The ZT510 features Zebra's world-renowned, high-quality print mechanisms and internal components to ensure flawless 24/7 performance, provide consistently outstanding quality and virtually eliminate costly downtime.

#### **Unrivalled durability in the toughest conditions**

With an all-metal design, rugged construction and sealed dome buttons to prevent ingress of dust, dirt and moisture, the ZT510 is right at home in today's harshest manufacturing and warehouse environments. This durable workhorse is engineered to withstand years of continuous operation, plus extreme temperatures, debris, rough handling and more.

#### **Value that won't break your budget**

The ZT510 is ideal for cost-conscious companies, offering next-generation print performance at an exceptional value. It provides high duty cycle, rugged reliability, fast processing, advanced Link-OS™ capabilities and all the basic features you need—without the added cost of those you don't. It's even ENERGY STAR® qualified to further protect your bottom line.

#### **A variety of connectivity options for flexible configuration**

Featuring a variety of standard communication options including USB, Serial, Gigabit Ethernet and Bluetooth® LE, the ZT510 is easy to integrate into existing systems and connect to various networks. Optional Parallel, 802.11a/c with Bluetooth® 4.0, USB Host and IPv6 are also available.

#### **Adaptability to meet evolving needs**

The ZT510 is engineered to grow and change with your business needs in the future by simplifying hardware upgrades, integrating seamlessly with common device management software and streamlining software updates with easy-to-use Link-OS applications.

#### **Additional capabilities that improve performance**

From the fast processor that enables quick throughput of even complex graphics to the optional USB Host card slot conveniently located on the back of the printer, the ZT510 optimizes performance at every turn. And dynamic QR codes provide additional "on-demand," web-based support to resolve printer errors quickly.



The ZT510 – Next-Gen Printing at a Budget-Friendly Value.  
For more information, visit [www.zebra.com/zt510](http://www.zebra.com/zt510)  
or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

# ZT510 Specifications

## Standard Features

- Print Methods: Thermal transfer and direct thermal printing
- Construction: Metal frame
- Thin film printhead with E<sup>3</sup>™ Element Energy™ Equalizer for superior print quality
- Communications: USB, Serial, Gigabit Ethernet, Bluetooth® LE
- Backlit, multi-line display including an intuitive menu, easy-to-use keypad and password protection

## Printer Specifications

Resolution	203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional)
Memory	512 MB RAM memory 2 GB on-board linear Flash memory
Maximum Print Width	4.09"/104 mm
Maximum Print Speed	12 ips/305 mm per second
Media Sensors	Dual media sensors: transmissive and reflective
Maximum Continuous Print Length	• 203 dpi: 150"/3810 mm • 300 dpi: 100"/2540 mm

## Media Characteristics

Media Width	0.79"/20 mm to 4.5"/114 mm
Maximum Media Roll Size	8.0"/203 mm O.D. on a 3"/76 mm I.D. core
Thickness	0.003"/0.076 mm to 0.012"/0.305 mm
Media Types	Continuous, die-cut, notch, black-mark

## Ribbon Characteristics

Standard Length	1476/450 m
Width	2.00"/51 mm to 4.33"/110 mm
Core	1.0"/25.4 mm I.D.

## Operating Characteristics

Environmental	Operating Temperature: <ul style="list-style-type: none"><li>• Thermal transfer = 40°F to 104°F/5°C to 40°C</li><li>• Direct thermal = 32°F to 104°F/0°C to 40°C</li></ul> Operating Humidity: 20% to 85% non-condensing Storage/Transportation Temperature: -22°F to 140°F/ -30°C to 60°C Storage Humidity: 20% to 85% non-condensing
Electrical	Auto-detectable (PFC Compliant) 90-265 VAC, 47-63Hz, rated at 250 Watts ENERGY STAR qualified
Agency Approvals	IEC 60950, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3 cTUVus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark (Arg), CCC, CU, BSMI, KCC, SABS, IN-Metro

## Physical Characteristics

Closed	
Length	20.17"/512.3 mm
Width	10.56"/268.2 mm
Height	15.58"/395.68 mm
Weight	50 lbs/22.7 kg

## Software Tools

### Link-OS Solutions

**Document Design** – Quickly design a customized print solution using your business data and Zebra's intuitive plug-and-print design tools.  
**Device Integration** – Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems.  
**Device Management** – Manage your print operations locally and globally with Zebra's suite of device management tools.  
**Developer Tools** – Provides you the tools you need to create your own apps, including documentation, source code, programming languages, templates and more.

### Web View

Connect and control Zebra barcode printers using ZPL II via the printer's web interface using common web browsers.

### Alert

Printers equipped with ZebraNet print servers will notify you via any email-enabled, wired or wireless device to minimize downtime.

## Firmware

**ZBI 2.0™** – Optional powerful programming language that lets printers run stand-alone applications, connect to peripherals and much more.

**ZPL and ZPL II®** – Zebra Programming Language provides sophisticated label formatting and printer control, and is compatible with all Zebra printers.

**XML-enabled Printing** – allows XML communications for barcode label printing.

## Barcode Symbologies

Linear Barcodes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2- or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code

2D Barcodes: Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec

## Fonts and Graphics

16 resident expandable ZPL II bitmap and two resident scalable ZPL fonts  
Asian and other international scalable and smooth bitmapped fonts

Unicode™: For multi-language printing

Downloadable objects include graphics, scalable and bitmap fonts, label templates and formats

IBM Code Page 850 international character sets are available in the fonts A, B, C, D, E, F, G and O through software control

Code Page 1250, 1252, 1253, 1254, 1255 Support with font 0

32 MB user available DRAM

512 MB user available on-board Flash

## Options and Accessories

### Connectivity

- Two open communication slots to add internal cards for 802.11ac, parallel, Ethernet. IPv6 option is available as an external dongle attached to a parallel port

### Media Handling

- Rewind: Internally rewinds a full roll of printed labels on 3" core, or peels and rewinds liner
- Cutter: Front-mount guillotine cutter and catch tray

### Keyboard Display Unit

- ZKDU™ keyboard display units for stand-alone printing applications

## Applications:

### Manufacturing

- Product identification labeling
- Packaging labeling
- Receiving/Put-away labeling
- Work-in-process

### Transportation & Logistics

- Order picking/packing
- Shipping/receiving
- Cross-docking
- Compliance labeling

## Additional Features:

### Near Field

### Communication (NFC)

Use with Print Touch Link-OS app to easily pair with Android devices.

### Backlit multi-line display

Customizable display includes an intuitive menu, easy-to-use keypad and password protection.

### Managed Visibility Services

Operational & Asset Visibility Services (OVS/AVS) offer important insights into the health, status, usage and performance of your printer.

### Field-installable upgrades

Communication card slots, cutter and peeler are easy to install in the field.

### Advanced troubleshooting

Onboard sensors, diagnostics and how-to videos enable guided troubleshooting.



NA and Corporate Headquarters  
+1 800 423 0442  
inquiry4@zebra.com

Asia-Pacific Headquarters  
+65 6858 0722  
contact.apac@zebra.com

EMEA Headquarters  
zebra.com/locations  
contact.emea@zebra.com

Latin America Headquarters  
+1 847 955 2283  
la.contactme@zebra.com